



RF24-105mm F4 L IS USM

- Lens control ring for fast intuitive shooting
- 5 stop Image Stabilizer
- Nano USM for movie shooting with quiet and smooth AF
- Uses a circular 9-blade aperture for exquisite soft-toned images
- Air Sphere Coating (ASC) reduces ghosting

no one sees it like you

Canon



TECHNICAL SPECIFICATIONS

RF24-105mm F4 L IS USM

Optical Features/Specifications		
Angle of view (horzntl, vertl, diagnl)		74°, 53°, 84°
Lens construction (elements/groups)		18/14
No. of diaphragm blades		9
Minimum aperture		f/4
Closest focussing distance (m)		0.45m
Maximum magnification (x)		0.24x
Distance Information		Via EVF or LCD
Air Sphere Coating (ASC)		YES
AF actuator		Nano USM
Physical Specifications		
Dust/moisture resistance		Yes ¹
Filter diameter (mm)		77mm
Max. diameter x length (mm)		83.5mm x 107.3mm
Weight (g)		700g
Accessories		
Lens cap		E-77II
Lens hood		EW-83N
Lens case/pouch		LP1319
Rear cap		Lens Dust Cap RF
Magnification with Extension Tube EF12 II		Not supported
Magnification with Extension Tube EF25 II		Not supported
Extender Compatibility		Not supported

¹ Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

For more information visit
canon.com.au
canon.co.nz

no one sees it like you

Canon